Technical Data Sheet



Ejoress®

SAFELY FAST-CHARGE BATTERIES ANYTIME DURING THE WORK DAY



Drivers can pull up and plug in anytime, including breaks and shift changes. The smart charging system of the Express® charger automatically recognizes the status of the batteries and keeps them optimally charged and equalized. Express chargers feature innovative Active Temperature/Output Management technology to ensure batteries receive optimal charging at every plug-in. Express chargers are equipped with a Wi-iQ® battery monitoring device to provide battery voltage and capacity data and adapt to a wide range of battery capacities, making it possible to reduce the number chargers in your fleet. Express chargers are California Energy Commission (CEC) compliant and UL certified.



AUTOMATIC BYPASSOF FAULTED MODULE

Continues charging process for uninterrupted operations



UP TO 94% EFFICIENCY

For maximum performance and energy savings





SMART AND FAST

Express® chargers increase productivity by quickly and safely charging fast-charge batteries anytime during the workday. They are designed exclusively for Express batteries.



				DC Max Output (Amps)				Input AC (Amps)		Max	Dimensions
	Cabinet Size	Cabinet Code	@ 24V	@ 36V	@ 48V	@ 72V	@ 80V	@ 480Vac	@ 600Vac	Weight (Ibs)	(W x D x H)
4 Bay	4	N	320	320	240	160	144	19.2	15.2	84	13.80" x 13.80" x 19.50"
6 Bay	6	Р	480	480	360	240	216	28.8	22.8	106	19.10" x 13.80" x 19.50"
8 Bay	8	R	640	640	480	320	288	38.4	30.4	197	15.95" x 14.80" x 37.80"
8 Bay Dual Port	8	R	2 @ 320	2 @ 320	2 @ 240	2 @ 160	2 @ 144	38.4	30.4	203	15.95" x 14.80" x 37.80"



